

YJQ-W2D Hand Crimp Tool Instruction

GENERAL INFORMATION

1. YJQ-W2D is which is widely used for the crimping of wires and contacts in electronic connectors.
2. Wire crimp range: 12AWG (3.33 mm²) to 26AWG (0.128 mm²).

Selector NO.	Intender Working Diameter mm/INCH	
	A (GO)	B (NO GO)
1	0.71/0.028	0.84/0.033
2	0.81/0.032	0.94/0.037
3	0.91/0.036	1.04/0.041
4	0.99/0.039	1.12/0.044
5	1.14/0.045	1.27/0.050
6	1.32/0.052	1.45/0.057
7	1.50/0.059	1.63/0.064
8	1.73/0.068	1.86/0.073



Crimping Sample



Indent Section View

WORKING PRINCIPLES

The crimping tool adopts curve propulsion mechanism, its applied force transfers through four curves in the head cavity of the right plier handle to the four indenters. The four indenters do the centripetal linear motion, which makes its front-end teeth crimp the contact to complete the crimping process. The cycle controlled precision ratchet assures the consistency of impression and the crimping quality of wires and contacts.

CRIMPING INSTRUCTIONS

1. Insert the contact and prepare the wire through the indenter from the opposite side.
2. Squeeze the handles together until ratchet releases. Then the handle will return to its open position automatically.

CAUTIONS

1. Keep the crimping tool and other units clean and properly stored when not in use or no operator maintenance.
2. Don't try to immerse tools in cleaning solution or spray oil into tools to lubricate.
3. If finding anomalies due to the incorrect ways, don't attempt to disassemble tools or make repairs. Please stop using it and connect us as soon as possible, our company will offer complete refurbishing and recalibration services.

